



# COMMERCIAL SLICER GL-350

Blade Ø 350 mm.



DYNAMIC PREPARATION  
GEAR DRIVEN SLICERS



## SPECIFICATIONS

Blade diameter: 350 mm

### Cutting capacity

- ✓ Square cut: 250 mm x 250 mm
- ✓ Round cut: 250 mm
- ✓ Rectangular cut: 250 mm x 300 mm

Slice thickness: 0 mm - 15 mm  
 Carriage run: 320 mm  
 Total loading: 430 W  
 IP Protection grade: 43

### External dimensions (WxDxH)

- ✓ Width: 800 mm
  - ✓ Depth: 580 mm
  - ✓ Height: 480 mm
- Net weight: 42 Kg  
 Noise level (1m.): 65 dB(A)

### Crated dimensions

840 x 630 x 650 mm

## SALES DESCRIPTION

Gear driven slicer.

### Gear driven commercial slicer with ring, carriage lock and blade removal tool.

- ✓ Slicer Fully made of high-polished aluminium protected against anodic oxidation.
- ✓ Built-in precision sharpener.
- ✓ Hard-chromed forged scoop knife.
- ✓ Life-lubricated helicoidal gear drive.
- ✓ Easy selection of cutting thickness.
- ✓ Bearing-mounted slide plate.
- ✓ Professional slicer with ring, carriage lock and blade removal tool.
- ✓ Heavy duty, ventilated motor.

Components in contact with food are completely detachable for easier cleaning.

## AVAILABLE MODELS

5050064 Slicer GL-350 230-400/50/3

5050070 Slicer GL-350 230/50/1

5050071 Slicer GL-350 220/60/1

5050073 Slicer GL-350 120/60/1

\* Ask for special versions availability



**sammic** | www.sammic.com  
Food Service Equipment Manufacturer

Polígono Basarte, 1. phone +34 943 15 72 36  
20720 Azkoitia, Spain sales@sammic.com



Project	Date
Item	Qty
Approved	

product sheet  
updated 13/07/2022